

It is a pneumatic valve controlled by micro electric signal. It can be installed in integration. It is an ideal direction control element, applicable to the electro-mechanical integration.

Ordering Code

TG	25	1	1	06	C		AC220V
Function	Valve body Code	Control Form	Pipe size	Working mode	Wiring type	Standard Voltage	
23 : - 2 positions/3 Ports	1: 1/8 2: 1/4 3: 3/8 4: 1/2	1: Single Solenoid Operated 2: Double solenoid operated	06 : Rc1/8 08 : Rc1/4 10 : Rc3/8 15 : Rc1/2	No mark: 2 positions C : Closed center E : Exhaust center P : Pressure Center	Bank : junction box K : leadwire with lamp	DC24V AC110V AC220V	



TG2511-06



TG2522-08



TG2531-10



TG2541-15

Ordering Code

TG	25	2	1	08	M	AC220V
Function	Valve body Code	Control Form	Pipe size	Installation Way	Standard Voltage	
25 : - 2 positions/5 Ports	2: 1/4 3: 3/8 4: 1/2	1: Single Solenoid Operated 2: Double solenoid operated	06 : Rc1/8 08 : Rc1/4 10 : Rc3/8 15 : Rc1/2	M : Namur Solenoid Valve	DC24V AC110V AC220V	

