



Features

- Durable Aluminium Housing Ergonomik Design
- High Torque Remove Tight Screw Easily
- Air Regulator For Positive Speed Control
- Forward/ Reverse Switch
- Quick-change Chuck For Loading Or Releasing Hex Bits Efficiently
- Top Quality Material And Precise Manufacturing Of Main Parts Ensure Tool Long Life
- Side Exhaust

Part No.	Description	Qty.	Part No.	Description	Qty.
01	Cdeducts Ring	2	26	Pin 2x8	1
02	Lock Set Liner	2	27	Pin 2x20	1
03	Fast Lock Is Covered	1	28	Bearing 626zz	1
04	Lock Set Spring	1	29	Body	1
05	Screw	3	30	Reverse Lever	1
06	Screw Washer	3	31	O-ring 8x1.8	2
07	It Is Former To Cover	1	32	O-ring 11.8x1.8	3
08	It Is Former To Cover Liner	1	33	O-ring	1
09	Contain Oil Cover	1	34	Close Open To Sell	1
10	Liner	1	35	Close Open To Sell Spring	1
11	Power Transmission Shaft Covers	1	36	O-ring 5.15x1.8	1
12	Steel Ball 1/8"	2	37	Close Open To Sell Spring	1
13	Power Transmission Shaft	1	38	Pin 2x18	1
14	Fix To Sell	2	39	O-ring 4.5x1.8	2
15	Bang Dozen Rooms	1	40	Regulate Knob	1
16	Bang Dozen Pieces	2	41	Spring	1
17	Bang Dozen Room Washers	1	42	Pin 2.5x10	1
18	Cam	1	43	Strain Dust Net	1
19	Locking Surrounds	1	44	Hook	1
20	Bearing Bo8zz	1	45	It Is Flexible To Sell	1
21	Front Plate	1	46	Trigger	1
22	Roter Blade	1	47	Air Inlet	1
23	Blade	6	48	O-ring	1
24	Cylinder	1	49	Contact	1
25	Rear Cover	1			

Specifications

Model	: AT-W5	AIR HOSE (ID)	: 3/8"
HEX SHANK SIZE	: 6.35 MM	AVG AIR CONSUMPTION	: 4 CFM
CAPACITY	: M5	WORKING PRESSURE	: 90 PSI
FREE SPEED	: 12000 RPM	LENGTH × HEIGHT	: 195×60
MAX TORQUE	: 100 NM	WEIGHT	: 0.70 KG
AIR INLET	: 1/4"		