



Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

MODEL	ØD	R	L1	L	L2	L3	ØD1	ØD2	H1	H2	↻
PKB04-MB	4	MS	3.5	66	42	22	13	3.2	19	9	10
PKB04-01	4	R1/8	7.5	68.5	42	22	13	3.2	19	9	10
PKB04-02	4	R1/4	9.5	71.5	42	22	13	3.2	19	9	14
PKB04-03	4	R3/8	10.5	72.5	42	22	15	S.2	19	9	17
PKB06-M5	6	M5	3.5	67	42	26	14.5	3.2	20.5	9	10
PKB06-01	6	R1/8	7.5	70	42	26	14.5	3.2	20.5	9	12
PKB06-02	6	R1/4	9.5	72	42	26	14.5	3.2	20.5	9	14
PKB06-03	6	R3/8	10.5	73	42	26	14.5	3.2	20.5	9	17
PKB06-04	6	R1/2	13.5	76.5	42	26	14.5	3.2	20.5	9	21
PKB08-01	8	R1/8	7.5	89	48	29	18.4	3.2	24	11	14
PKB08-02	8	R1/4	9.5	91	48	29	18.4	3.2	24	11	14
PKB08-03	8	R3/8	10.5	92.5	48	29	18.4	3.2	24	11	17
PKB08-04	8	R1/2	13.5	96	48	29	18.4	3.2	24	11	21
PKB10-01	10	R1/8	7.5	100	60.8	36.8	18.4	4.2	28.5	11	17
PKB10-02	10	R1/4	9.5	102	60.8	36.8	18.4	4.2	28.5	11	17
PKB10-03	10	R3/8	10.5	103	60.8	36.8	18.4	4.2	28.5	11	17
PKB10-04	10	R1/2	13.5	106.5	60.8	36.8	18.4	4.2	28.5	11	21

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F 0~60°C	