



Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

| MODEL | ØD | R | L1 | L | L2 | L3 | ØD1 | ØD2 | H1 | H2 |
|-------|----|----|------|------|-----|----|-----|-----|------|------|
| PK04 | 4 | 4 | 14.5 | 13 | 3.2 | 57 | 36 | 22 | 19 | 8 |
| PK06 | 6 | 6 | 14.5 | 13 | 3.2 | 58 | 36 | 22 | 19.5 | 8 |
| PK08 | 8 | 8 | 19 | 14.5 | 4.2 | 84 | 61 | 29 | 24.5 | 11.5 |
| PK10 | 10 | 10 | 19 | 14.5 | 4.2 | 87 | 61 | 29 | 26 | 11.5 |
| PK12 | 12 | 12 | 23 | 16 | 4.2 | 90 | 70 | 32 | 29 | 12.5 |

Specifications

| Fluid Type | Air (No other type of gas or liquid) | |
|------------------------|--------------------------------------|-------------------------------------|
| Working Pressure Range | 0~150PSI | 0~9.8Kgf/cm ² (0~990KPa) |
| Negative Pressure | -29.5 in Hg | -750mm Hg (10 Torr) |
| Working Temperature | 32~140°F | 0~60°C |