



Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

MODEL	ØD	R	L1	L2	L3	ØD1	↻
PLL04-M5	4	MS	3.5	33.3	19	11.5	10
PLL04-M6	4	M6	4	33.8	19	11.5	10
PLL04-01	4	R1/8	7.5	35.8	19	11.5	10
PLL04-02	4	R1/4	9.5	58.8	19	11.5	14
PLL06-M5	6	M5	3.5	35	19.2	13.5	12
PLL06-M6	6	M6	4	35.5	19.2	13.5	12
PLL06-01	6	R1/8	7.5	38.2	19.2	13.5	12
PLL06-02	6	R1/4	9.5	40.7	19.2	13.5	14
PLL06-03	6	R3/8	10.5	42.2	19.2	13.5	17
PLL06-04	6	R1/2	13.5	45.7	19.2	13.5	21
PLL08-01	8	R1/8	7.5	42.8	22.5	15	14
PLL08-02	8	R1/4	9.5	44.8	22.5	15	14
PLL08-03	8	R3/8	10.5	46.4	22.5	15	17
PLL08-04	8	R1/2	13.5	48.8	22.5	15	21
PLL10-01	10	R1/8	7.5	52.3	27.8	19	17
PLL10-02	10	R1/4	9.5	54.3	27.8	19	17
PLL10-03	10	R3/8	10.5	55.3	27.8	19	17
PLL10-04	10	R1/2	13.5	58.8	27.8	19	21
PLL12-01	12	R1/8	7.5	57	29.5	21.5	21
PLL12-02	12	R1/4	9.5	59	29.5	21.5	21
PLL12-03	12	R3/8	10.5	60	29.5	21.5	21
PLL12-04	12	R1/2	13.5	63	29.5	21.5	21

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C