



Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

| MODEL | ØD | R | L1 | L2 | L3 | L4 | ØD1 | ↻ |
|----------|----|------|------|------|------|------|------|----|
| PST04-M5 | 4 | MS | 3.5 | 21.3 | 40.3 | 19 | 11.5 | 10 |
| PST04-M6 | 4 | M6 | 4 | 21.8 | 40.8 | 19 | 11.5 | 10 |
| PST04-01 | 4 | R1/8 | 7.5 | 23.8 | 42.8 | 19 | 11.5 | 10 |
| PST04-02 | 4 | R1/4 | 9.5 | 26.8 | 45.8 | 19 | 1L5 | 14 |
| PST04-03 | 4 | R3/8 | 10.5 | 28.3 | 47.3 | 19 | 11.5 | 17 |
| PST06-M5 | 6 | M5 | 3.5 | 21.7 | 40.9 | 19.2 | 13.5 | 12 |
| PST06-M6 | 6 | M6 | 4 | 22.2 | 41.4 | 19.2 | 13.5 | 12 |
| PST06-01 | 6 | R1/8 | 7.5 | 24.2 | 43.4 | 19.2 | 13.5 | 12 |
| PST06-02 | 6 | R1/4 | 9.5 | 26.7 | 46 | 19.2 | 13.5 | 14 |
| PST06-03 | 6 | R3/8 | 10.5 | 28.2 | 47.5 | 19.2 | 13.5 | 17 |
| PST06-04 | 6 | R1/2 | 13.5 | 31.7 | 51 | 19.2 | 13.5 | 21 |
| PST08-01 | 8 | R1/8 | 7.5 | 27.5 | 50 | 22.5 | 15 | 14 |
| PST08-02 | 8 | R1/4 | 9.5 | 29.5 | 52 | 22.5 | 15 | 14 |
| PST08-03 | 8 | R3/8 | 10.5 | 31 | 53.5 | 22.5 | 15 | 17 |
| PST08-04 | 8 | R1/2 | 13.5 | 34.5 | 57 | 22.5 | 15 | 21 |
| PST10-01 | 10 | R1/8 | 7.5 | 33 | 61.5 | 27.8 | 19 | 17 |
| PST10-02 | 10 | R1/4 | 9.5 | 35 | 63.5 | 27.8 | 19 | 17 |
| PST10-03 | 10 | R3/8 | 10.5 | 36 | 64.5 | 27.8 | 19 | 17 |
| PST10-04 | 10 | R1/2 | 13.5 | 39.5 | 68 | 27.8 | 19 | 21 |
| PST12-01 | 12 | R1/8 | 7.5 | 33.5 | 63 | 29.5 | 21.5 | 21 |
| PST12-02 | 12 | R1/4 | 9.5 | 36 | 65.5 | 29.5 | 21.5 | 21 |
| PST12-03 | 12 | R3/8 | 10.5 | 37 | 66.5 | 29.5 | 21.5 | 21 |
| PST12-04 | 12 | R1/2 | 13.5 | 40 | 69.5 | 29.5 | 21.5 | 21 |

Specifications

| Fluid Type | Air (No other type of gas or liquid) | |
|------------------------|--------------------------------------|-------------------------------------|
| Working Pressure Range | 0~150PSI | 0~9.9Kgf/cm ² (0~990KPa) |
| Negative Pressure | -29.5 in Hg | -750mm Hg(10 Torr) |
| Working Temperature | 32~140°F | 0~60°C |