



Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

MODEL	ØD	R	L1	L2	L3	ØD1	↻
PT04-M5	4	M5	3.5	21.3	38	11.5	10
PT04-M6	4	M6	4	21.8	38	11.5	10
PT04-01	4	R1/8	7.5	23.8	38	11.5	10
PT04-02	4	R1/4	9.5	29.8	38	11.5	14
PT04-03	4	R3/8	10.5	28.3	38	11.5	17
PT06-M5	6	M5	3.5	21.7	59	13.5	12
PT06-M6	6	M6	4	22.2	39	13.5	12
PT06-01	6	R1/8	7.5	24.2	39	13.5	12
PT06-02	6	R1/4	9.5	26.7	39	13.5	14
PT06-03	6	R3/8	10.5	28.2	59	13.5	17
PT06-04	6	R1/2	13.5	31.7	39	13.5	21
PT08-01	8	R1/8	7.5	27.5	45	15	14
PT08-02	8	R1/4	9.5	29.5	45	15	14
PT08-03	8	R3/8	10.5	31	45	15	17
PT08-04	8	R1/2	13.5	34.5	45	15	21
PT10-01	10	R1/8	7.5	32.8	57	19	17
PT10-02	10	R1/4	9.5	34.8	57	19	17
PT10-03	10	R3/8	10.5	35.8	57	19	17
PT10-04	10	R1/2	13.5	39.3	57	19	21
PT12-01	12	R1/8	7.5	33.5	59	21.5	21
PT12-02	12	R1/4	9.5	36	59	21.5	21
PT12-03	12	R3/8	10.5	37	59	21.5	21
PT12-04	12	R1/2	13.5	40	59	21.5	21
PT14-03	14	R3/8	10.5	41	54	23.5	22
PT14-04	14	R1/2	13.5	44	54	23.5	22
PT15-03	15	R3/8	10.5	44	66	26.5	24
PT15-04	15	R1/2	13.5	47	66	26.5	24
PT16-03	16	R3/8	10.5	44	66	26.5	24
PT16-04	16	R1/2	13.5	47	66	26.5	24

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F 0~60°C	